



Ventilazione - Ventilation - Ventilation	IC 06 - IC 17	Protezione - Enclosure - Protection	IP 23S
	IC 37		IP 44 - IP 54 - IP 55
	IC W37 A 86		IP 44 - IP 54 - IP 55

P eccitazione - P excitation - P excitation	L1	2680	W	Massa motore - Mass of motor - Masse moteur	1020	kg
	L3	3840	W	Mom. d'inerzia - Mom. of inertia - Mom. inertie	2,6	kg m ²
Cost. tempo ecc. - Exc. time cost. - Const. temps exc.	L1	650	ms	Portata aria - Air flow - Débit d'air	0,75	m ³ /s
	L3	440	ms	Caduta pressione - Pressure drop - Chute de pression	16	mb

Code	Va	400	440	460	520	550	600	P	I	η	T	R	R	L	L	n	n
		velocità base - base speed - vitesse de base [rpm]						[kW]	[A]	[%]	[Nm]	115 °C L1	115 °C L3	L1	L3	max L1	max L3
2F5		1635						346	922	93,8	2021					2627	3000
		1805						379	916	94,2	2005					2645	3000
			1891					396	912	94,3	2000	15,3	17,7	0,731	0,182	2657	3000
				2148				441	895	94,7	1961					2706	3000
					2276			461	885	94,8	1934					2738	3000
						2491		492	863	95,0	1886					2807	3000
2G5		1467						312	838	93,1	2031					2406	3000
		1622						344	835	93,5	2026					2416	3000
			1699					359	832	93,7	2018	20,5	22,2	0,924	0,276	2422	3000
				1931				403	823	94,2	1993					2450	3000
					2047			424	816	94,4	1978					2470	3000
						2241		456	803	94,7	1943					2511	3000
A0 1 2		1352						288	774	93,1	2034					2609	3000
		1494						318	772	93,6	2033					2616	3000
			1565					332	770	93,8	2026	22,1	23,7	1,06	0,34	2621	3000
				1779				375	764	94,3	2013					2642	3000
					1886			395	760	94,5	2000					2656	3000
						2064		427	751	94,7	1976					2688	3000
B0 1 2		1216						260	701	92,6	2041					2397	3000
		1345						287	700	93,2	2038					2400	3000
			1409					300	699	93,4	2033	27,4	30,3	1,31	0,38	2403	3000
				1602				340	696	93,9	2026					2414	3000
					1699			359	694	94,2	2018					2422	3000
						1860		390	688	94,5	2002					2440	3000
C0 1 2		1104						236	640	92,1	2042					2205	3000
		1221						261	640	92,7	2041					2206	3000
			1280					273	640	92,9	2037	33,5	35,9	1,58	0,53	2207	3000
				1456				310	638	93,5	2033					2213	3000
					1544			328	637	93,8	2028					2218	3000
						1691		358	634	94,1	2021					2228	3000
D 2		1000						214	581	91,9	2043					2604	3000
		1107						237	581	92,5	2045					2605	3000
			1160					248	581	92,8	2041	38,2	42,3	1,89	0,57	2605	3000
				1320				282	580	93,4	2040					2608	3000
					1400			299	580	93,7	2040					2611	3000
						1533		326	578	94,1	2030					2619	3000
E 2		898						192	526	91,2	2042					2396	3000
		994						213	526	91,9	2046					2396	3000
			1042					223	526	92,2	2043	47,8	53	2,33	0,68	2396	3000
				1187				254	526	92,9	2043					2397	3000
					1259			269	525	93,2	2040					2398	3000
						1380		295	525	93,6	2041					2402	3000
F		786						168	465	90,3	2040					2604	2988
		872						186	465	91,1	2038					2604	3000
			914					196	465	91,4	2047	61,6	65,8	2,97	1,03	2604	3000
				1042				223	465	92,2	2043					2604	3000
					1106			237	465	92,6	2046					2605	3000
						1213		259	465	93,1	2040					2606	3000



Ventilazione - Ventilation - Ventilation	IC 06 - IC 17	Protezione - Enclosure - Protection	IP 23S
	IC 37		IP 44 - IP 54 - IP 55
	IC W37 A 86		IP 44 - IP 54 - IP 55

P eccitazione - P excitation - P excitation	L1	2680	W	Massa motore - Mass of motor - Masse moteur	1020	kg
	L3	3840	W	Mom. d'inerzia - Mom. of inertia - Mom. inertie	2,6	kg m ²
Cost. tempo ecc. - Exc. time cost. - Const. temps exc.	L1	650	ms	Portata aria - Air flow - Débit d'air	0,75	m ³ /s
	L3	440	ms	Caduta pressione - Pressure drop - Chute de pression	16	mb

Code	Va	400	440	460	520	550	600	P	I	η	T	R	R	L	L	n	n
		velocità base - base speed - vitesse de base [rpm]						[kW]	[A]	[%]	[Nm]	115 °C L1 [mOhm]	115 °C L3 [mOhm]	L1 [mH]	L3 [mH]	max L1 [rpm]	max L3 [rpm]
G	2	703						150	421	89,3	2037					2396	2672
		780						167	421	90,1	2044					2396	2965
			819					175	421	90,5	2041	78,4	86,4	3,64	1,06	2396	3000
				934				200	421	91,4	2044					2396	3000
					992			212	421	91,8	2040					2396	3000
						1089		233	421	92,4	2044					2396	3000
H	2	635						136	384	88,3	2045					2205	2413
		705						151	384	89,2	2044					2205	2680
			741					158	384	89,6	2037	96,2	102,8	4,36	1,44	2205	2814
				846				181	384	90,7	2043					2205	3000
					899			192	384	91,1	2039					2205	3000
						987		211	384	91,7	2041					2205	3000
K	2	575						120	342	87,9	1991					1198	1851
		640						134	342	88,9	2001					1198	1851
			672					141	342	89,3	2005	112	124	5,49	1,65	1198	1851
				768				161	342	90,4	2003					1198	1851
					816			171	342	90,8	2002					1198	1851
						896		188	342	91,5	2004					1198	1851
L	2	520						109	313	86,8	2002					1102	1704
		579						121	313	87,9	1997					1102	1704
			608					127	313	88,3	1995	137	147	6,6	2,27	1102	1704
				696				146	313	89,5	2004					1102	1704
					740			155	313	90,0	2001					1102	1704
						813		171	313	90,7	2009					1102	1704
M	2	468						97,9	283	86,4	1998					1302	1778
		521						109	283	87,5	1998					1302	1979
			547					115	283	88,0	2006	157	173	8,01	2,53	1302	2012
				627				131	283	89,2	1996					1302	2012
					667			140	283	89,7	2006					1302	2012
						733		154	283	90,5	2007					1302	2012
N	2	417						87,3	257	84,9	1998					1198	1586
		465						97,4	257	86,2	1999					1198	1768
			489					102	257	86,7	1990	196	217	9,79	2,96	1198	1851
				561				118	257	88,1	2007					1198	1851
					597			125	257	88,7	1998					1198	1851
						658		138	257	89,5	2004					1198	1851
O	2	361						75,4	227	83,2	1996					1302	1371
		403						84,3	227	84,6	1997					1302	1532
			424					88,8	227	85,2	1999	253	269	12,5	4,5	1302	1612
				488				102	227	86,8	1997					1302	1854
					520			109	227	87,4	2003					1302	1975
						573		120	227	88,3	2001					1302	2012
P	2	319						66,6	205	81,0	1995					1198	1211
		357						74,7	205	82,6	1997					1198	1357
			376					78,8	205	83,3	1999	321	354	15,3	4,6	1198	1430
				434				90,9	205	85,1	2000					1198	1649
					463			97	205	85,8	2001					1198	1759
						511		107	205	86,9	2000					1198	1851

2 = componenti a magazzino - components in stock - composant en stock