



Ventilazione - Ventilation - Ventilation	IC 06 - IC 17	Protezione - Enclosure - Protection	IP 23S
	IC 37		IP 44 - IP 54 - IP 55
	IC W37 A 86		IP 44 - IP 54 - IP 55

P eccitazione - P excitation - P excitation	L1	4550	W	Massa motore - Mass of motor - Masse moteur	1650	kg
	L3	4550	W	Mom. d'inerzia - Mom. of inertia - Mom. inertie	4,65	kg m ²
Cost. tempo ecc. - Exc. time cost. - Const. temps exc.	L1	460	ms	Portata aria - Air flow - Débit d'air	1,5	m ³ /s
	L3	460	ms	Caduta pressione - Pressure drop - Chute de pression	18	mb

Code	Va	400	440	460	520	550	600	P	I	η	T	R	R	L	L	n	n
	velocità base - base speed - vitesse de base [rpm]							[kW]	[A]	[%]	[Nm]	115 °C L1 [mOhm]	115 °C L3 [mOhm]	L1 [mH]	L3 [mH]	max L1 [rpm]	max L3 [rpm]
2A <i>I</i>	2177							592	1560	94,9	2597						2600
	2400							653	1560	95,1	2598						2600
	2512							683	1560	95,1	2596		5,25		0,0721		2600
2B <i>I</i>	1990							590	1560	94,5	2831						2600
	2196							650	1560	94,8	2827						2600
	2299							681	1560	94,9	2829		6,8		0,0647		2600
2C <i>I</i>	1835							588	1560	94,2	3060						2600
	2025							649	1560	94,6	3060						2600
	2121							679	1558	94,7	3057		7,84		0,0852		2600
	2412							702	1421	95,0	2780						2600
	2557							701	1339	95,1	2618						2600
A <i>I</i>	1607							568	1513	93,9	3376						2600
	1776							612	1475	94,3	3291						2600
	1861							631	1452	94,5	3238		9,48		0,135		2600
	2115							677	1370	95,0	3056						2600
B	1467							493	1324	93,2	3209						2507
	1623							535	1299	93,7	3148						2555
	1701							555	1284	93,9	3117		13		0,127		2585
	1935							604	1230	94,4	2981						2600
	2052							624	1198	94,6	2904						2600
C	1357							476	1279	93,1	3351						2355
	1500							519	1261	93,6	3303						2390
	1572							539	1250	93,8	3274		13,9		0,161		2411
	1788							594	1209	94,4	3172						2492
	1897							617	1185	94,6	3106						2543
	2078							648	1137	94,9	2978						2600
D	1254							433	1172	92,4	3296						2295
	1388							474	1159	93,0	3261						2321
	1455							494	1151	93,3	3242		17,3		0,164		2337
	1656							548	1123	93,9	3160						2397
	1757							572	1105	94,2	3109						2435
	1925							607	1071	94,5	3011						2514
E	1172							419	1133	92,4	3413						2125
	1297							459	1123	93,0	3379						2144
	1360							479	1117	93,2	3364		18,3		0,201		2155
	1548							534	1095	93,9	3295						2199
	1642							560	1081	94,1	3257						2226
	1799							598	1054	94,5	3175						2283

I = avvolgimenti speciali - special windings - enroulements spécial



Ventilazione - Ventilation - Ventilation	IC 06 - IC 17	Protezione - Enclosure - Protection	IP 23S
	IC 37		IP 44 - IP 54 - IP 55
	IC W37 A 86		IP 44 - IP 54 - IP 55

P eccitazione - P excitation - P excitation	L1	4550	W	Massa motore - Mass of motor - Masse moteur	1650	kg
	L3	4550	W	Mom. d'inerzia - Mom. of inertia - Mom. inertie	4,65	kg m ²
Cost. tempo ecc. - Exc. time cost. - Const. temps exc.	L1	460	ms	Portata aria - Air flow - Débit d'air	1,5	m ³ /s
	L3	460	ms	Caduta pressione - Pressure drop - Chute de pression	18	mb

Code	Va	400	440	460	520	550	600	P	I	η	T	R	R	L	L	n	n
	velocità base - base speed - vitesse de base [rpm]							[kW]	[A]	[%]	[Nm]	115 °C L1 [mOhm]	115 °C L3 [mOhm]	L1 [mH]	L3 [mH]	n max L1 [rpm]	n max L3 [rpm]
F	1045							375	1022	91,6	3427						2600
	1157							413	1016	92,3	3409						2600
	1213							431	1012	92,6	3393		23,3		0,237		2600
	1382							485	999	93,3	3352						2600
	1466							510	990	93,6	3322						2600
	1607							549	973	94,0	3263						2600
H	881							324	892	90,7	3512						2298
	976							358	889	91,5	3502						2305
	1024							375	887	91,8	3497		31		0,341		2309
	1167							424	881	92,6	3468						2326
	1239							448	877	92,9	3453						2337
	1359							487	868	93,4	3423						2360
J	767							278	774	89,7	3461						2593
	851							308	773	90,5	3457						2597
	893							323	772	90,9	3455		41		0,445		2600
	1019							367	768	91,8	3440						2600
	1082							388	766	92,2	3425						2600
	1187							424	762	92,7	3411						2600
L	645							231	654	88,5	3421						2351
	716							257	653	89,4	3426						2353
	752							270	653	89,9	3428		55,8		0,663		2354
	859							308	652	90,9	3423						2359
	913							327	651	91,3	3420						2362
	1002							358	649	91,9	3410						2369
N	553							195	559	87,0	3370						2100
	615							217	559	88,1	3371						2154
	646							228	559	88,6	3371		75,8		0,804		2154
	739							260	558	89,7	3359						2156
	786							277	558	90,2	3366						2158
	864							304	557	90,9	3361						2161
P	483							172	504	85,4	3399						1300
	539							192	504	86,6	3404						1300
	566							202	504	87,2	3406		96,9		1,02		1300
	650							232	503	88,5	3411						1300
	691							247	503	89,1	3413						1301
	760							271	503	89,9	3403						1302
R	405							145	432	83,7	3419						1165
	452							162	432	85,1	3420						1165
	476							170	432	85,7	3410		129		1,39		1165
	547							196	432	87,2	3421						1165
	583							208	432	87,8	3409						1165
	642							230	431	88,7	3422						1166
T	347							125	383	81,7	3440						1282
	389							140	383	83,3	3440						1282
	409							148	383	83,9	3452		166		1,9		1282
	472							171	383	85,7	3462						1282
	503							182	383	86,4	3456						1282
	555							201	383	87,4	3460						1282