



Ventilazione - Ventilation - Ventilation	IC 06 - IC 17	Protezione - Enclosure - Protection	IP 23S
	IC 37		IP 44 - IP 54 - IP 55
	IC W37 A 86		IP 44 - IP 54 - IP 55

P eccitazione - P excitation - P excitation	L3	5050	W	Massa motore - Mass of motor - Masse moteur	2830	kg
Cost. tempo ecc. - Exc. time cost. - Const. temps exc.	L3	640	ms	Mom. d'inerzia - Mom. of inertia - Mom. inertie	11,1	kg m ²
				Portata aria - Air flow - Débit d'air	2	m ³ /s
				Caduta pressione - Pressure drop - Chute de pression	20	mb

Code	Va	400	440	460	520	600	700	P	I	η	T	R	L	n
		velocità base - base speed - vitesse de base [rpm]						[kW]	[A]	[%]	[Nm]	115 °C L3 [mOhm]	L3 [mH]	max L3 [rpm]
2A <i>I</i>		1389						605	1600	94,6	4158			2400
		1533						668	1600	94,9	4161			2400
			1605					699	1600	95,0	4160	6,5	0,103	2400
				1820				793	1600	95,3	4161			2400
					2107			917	1600	95,5	4156			2400
2B <i>I</i>		1270						602	1600	94,0	4527			2294
		1402						665	1600	94,4	4530			2294
			1468					696	1600	94,6	4528	8,1	0,0868	2294
				1666				790	1600	94,9	4529			2294
					1930			915	1600	95,3	4528			2294
2C <i>I</i>		1172						600	1600	93,8	4890			1990
		1294						663	1600	94,2	4893			1990
			1355					695	1600	94,4	4898	8,92	0,119	1990
				1538				789	1600	94,8	4897			1990
					1783			914	1600	95,2	4895			1990
2D <i>I</i>		1088						599	1600	93,6	5258			1788
		1202						662	1600	94,1	5261			1788
			1259					694	1600	94,3	5266	9,59	0,146	1788
				1429				788	1600	94,7	5265			1788
					1657			914	1600	95,2	5268			1788
2E <i>I</i>		1012						596	1600	93,2	5624			1548
		1119						659	1600	93,7	5626			1548
			1172					691	1600	93,9	5631	10,9	0,195	1548
				1331				785	1600	94,4	5630			1548
					1545			890	1562	95,0	5499			1585
B0 <i>I</i>		932						563	1525	92,3	5769			1805
		1031						621	1519	92,9	5751			1813
			1081					649	1515	93,1	5734	13,9	0,171	1817
				1230				732	1501	93,8	5684			1834
C0 <i>I</i>		861						521	1415	92,0	5780			1688
		953						575	1411	92,7	5765			1693
			998					602	1408	92,9	5758	15,7	0,226	1696
				1136				681	1399	93,6	5723			1708
					1320			780	1379	94,3	5641			1731
2F		804						487	1330	91,6	5782			1854
		890						539	1328	92,2	5780			1858
			934					564	1326	92,5	5769	18,1	0,211	1861
				1063				639	1319	93,2	5740			1871
					1236			736	1305	94,0	5688			1891
						1452		847	1278	94,6	5570			1930

I = avvolgimenti speciali - special windings - enroulements spécial



STILPAF
MURARO S.p.A.
Zermeghedo - Vicenza

Ventilazione - Ventilation - Ventilation	IC 06 - IC 17	Protezione - Enclosure - Protection	IP 23S
	IC 37		IP 44 - IP 54 - IP 55
	IC W37 A 86		IP 44 - IP 54 - IP 55

P eccitazione - P excitation - P excitation	L3	5050	W	Massa motore - Mass of motor - Masse moteur	2830	kg
				Mom. d'inerzia - Mom. of inertia - Mom. inertie	11,1	kg m ²
Cost. tempo ecc. - Exc. time cost. - Const. temps exc.	L3	640	ms	Portata aria - Air flow - Débit d'air	2	m ³ /s
				Caduta pressione - Pressure drop - Chute de pression	20	mb

Code	Va	400	440	460	520	600	700	P	I	η	T		R		L		n
		velocità base - base speed - vitesse de base [rpm]											115 °C L3 [mOhm]		L3 [mH]		max L3 [rpm]
E		741	821	861	981	1141	1342	450	1235	91,0	5797		21,3		0,285		1504
								498	1233	91,7	5791						1506
								522	1232	92,0	5789						1507
								592	1228	92,8	5762						1513
								684	1218	93,6	5723						1525
								792	1199	94,3	5637						1549
F		659	731	767	874	1018	1198	400	1111	90,0	5798		27,4		0,31		1851
								444	1110	90,8	5803						1852
								465	1109	91,1	5793						1853
								530	1107	92,0	5789						1857
								614	1101	92,9	5759						1867
								715	1090	93,8	5699						1886
G		605	671	704	804	936	1101	368	1022	89,9	5805		30,2		0,435		1795
								408	1022	90,7	5803						1796
								428	1022	91,0	5802						1797
								488	1020	91,9	5800						1799
								566	1016	92,8	5776						1806
								662	1009	93,7	5741						1819
H		555	616	647	739	861	1014	337	947	89,0	5797		36,3		0,452		1682
								374	947	89,9	5796						1682
								393	946	90,3	5802						1682
								449	946	91,3	5806						1684
								522	943	92,3	5790						1688
								612	938	93,2	5764						1697
J		483	537	564	645	752	887	293	834	88,0	5789		46,1		0,596		1837
								326	834	89,0	5796						1850
								343	834	89,4	5807						1850
								392	833	90,5	5806						1851
								457	832	91,6	5800						1853
								538	830	92,6	5791						1858
K		442	492	516	591	690	813	268	767	87,5	5790		52,9		0,775		1680
								299	767	88,5	5809						1795
								314	767	88,9	5808						1795
								359	767	90,1	5805						1795
								419	766	91,2	5802						1796
								494	765	92,3	5799						1800
L		405	451	474	542	634	749	246	710	86,5	5804		62,7		0,906		1538
								274	710	87,6	5807						1682
								288	710	88,1	5808						1682
								330	710	89,3	5811						1682
								386	710	90,6	5814						1682
								455	709	91,7	5804						1684
M		372	415	436	500	586	693	226	661	85,4	5795		73,6		1,01		1415
								252	661	86,7	5797						1577
								265	661	87,2	5798						1623
								304	661	88,5	5801						1623
								356	661	89,9	5803						1623
								421	661	91,1	5805						1624