

400 S



STIPAF
MURARO S.p.A.
Zermeghedo - Vicenza

Ventilazione - Ventilation - Ventilation	IC 06 - IC 17	Protezione - Enclosure - Protection	IP 23S
	IC 37		IP 44 - IP 54 - IP 55
	IC W37 A 86		IP 44 - IP 54 - IP 55

P eccitazione - P excitation - P excitation	L3	4760	W	Massa motore - Mass of motor - Masse moteur	3400	kg
				Mom. d'inerzia - Mom. of inertia - Mom. inertie	25,5	kg m ²
Cost. tempo ecc. - Exc. time cost. - Const. temps exc.	L3	1000	ms	Portata aria - Air flow - Débit d'air	2,8	m ³ /s
				Caduta pressione - Pressure drop - Chute de pression	22	mb

Code	Va	400	440	460	520	600	700	P	I	η	T		R		L		n
													115 °C L3		L3		max L3
								[kW]	[A]	[%]	[Nm]		[mOhm]		[mH]		[rpm]
2A0 <i>l</i>		1093						962	2560	94,0	8404						1776
		1207						1063	2560	94,4	8409						1776
			1264					1114	2560	94,6	8415		5,58		0,0613		1776
				1436				1254	2538	95,0	8341						1791
					1665			1409	2460	95,5	8081						1848
						1952		1559	2322	95,9	7626						1957
2B0 <i>l</i>		1003						905	2414	93,8	8616						1643
			1108					995	2401	94,2	8574						1651
				1161				1039	2393	94,4	8547		6,33		0,0811		1657
					1319			1167	2364	94,9	8451						1677
						1529		1321	2309	95,4	8248						1717
2C0 <i>l</i>		927						839	2241	93,6	8641						1581
			1025					924	2233	94,1	8612						1587
				1073				966	2227	94,3	8596		7,1		0,11		1591
					1219			1088	2207	94,8	8521						1606
						1414		1240	2167	95,3	8373						1635
							1658	1406	2097	95,8	8096						1689
2D0 <i>l</i>		862						782	2091	93,5	8664						1519
			953					862	2085	94,0	8642						1523
				998				902	2081	94,2	8632		7,89		0,136		1526
					1134			1018	2067	94,7	8575						1537
						1315		1165	2038	95,2	8459						1558
							1542	1331	1987	95,7	8242						1599
2E		801						727	1959	92,8	8672						1476
			885					803	1955	93,3	8662						1479
				928				840	1952	93,6	8648		9,83		0,119		1481
					1055			951	1942	94,2	8610						1489
						1224		1093	1921	94,8	8525						1505
							1437	1257	1883	95,3	8355						1535
B		743						676	1823	92,6	8685						1631
			822					747	1821	93,2	8678						1633
				861				782	1819	93,4	8669		10,9		0,16		1635
					980			886	1812	94,1	8637						1641
C		687						625	1690	92,5	8687						1573
			760					691	1688	93,1	8683						1575
				796				724	1687	93,3	8681		12,1		0,211		1576
					906			822	1682	93,9	8666						1580
						1052		949	1672	94,6	8617						1589
D		636						578	1574	91,9	8683						1514
			703					640	1573	92,5	8687						1515
				737				671	1572	92,8	8689		14,5		0,193		1515
					839			763	1569	93,5	8682						1518
						975		883	1562	94,2	8647						1525

l = avvolgimenti speciali - special windings - enroulements spécial



STILPAF
MURARO S.p.A.
Zermeghedo - Vicenza

Ventilazione - Ventilation - Ventilation	IC 06 - IC 17	Protezione - Enclosure - Protection	IP 23S
	IC 37		IP 44 - IP 54 - IP 55
	IC W37 A 86		IP 44 - IP 54 - IP 55

P eccitazione - P excitation - P excitation	L3	4760	W	Massa motore - Mass of motor - Masse moteur	3400	kg
				Mom. d'inerzia - Mom. of inertia - Mom. inertie	25,5	kg m²
Cost. tempo ecc. - Exc. time cost. - Const. temps exc.	L3	1000	ms	Portata aria - Air flow - Débit d'air	2,8	m³/s
				Caduta pressione - Pressure drop - Chute de pression	22	mb

Code	Va	400	440	460	520	600	700	P	I	η	T		R		L		n
		velocità base - base speed - vitesse de base [rpm]											115 °C L3 [mOhm]		L3 [mH]		max L3 [rpm]
E		593	657	688	784	911	1070	540	1472	91,7	8694		16,2		0,26		1473
								598	1472	92,3	8697						1473
								627	1471	92,6	8698						1474
								713	1470	93,3	8689						1476
								826	1465	94,0	8662						1480
								965	1455	94,7	8616						1490
F		553	612	642	732	851	1000	503	1383	90,9	8690		19,4		0,249		1388
								558	1383	91,6	8702						1388
								585	1383	91,9	8699						1389
								666	1382	92,7	8693						1390
								774	1378	93,5	8686						1393
								905	1372	94,3	8641						1400
G		481	534	560	639	744	875	438	1217	89,9	8693		25,3		0,324		1628
								486	1217	90,7	8697						1628
								510	1217	91,1	8699						1628
								582	1217	92,0	8704						1629
								677	1216	92,9	8695						1631
								795	1212	93,7	8678						1635
H		444	493	517	590	687	809	404	1127	89,7	8683		28,2		0,418		1572
								449	1127	90,5	8699						1572
								471	1127	90,9	8697						1572
								538	1127	91,8	8707						1572
								627	1126	92,7	8713						1573
								736	1124	93,6	8691						1576
I		410	456	478	546	636	750	373	1049	88,9	8681		33,2		0,455		1513
								415	1049	89,8	8700						1513
								435	1049	90,2	8688						1513
								498	1049	91,2	8710						1513
								580	1049	92,2	8703						1514
								683	1048	93,1	8702						1515
K		356	395	415	475	554	654	323	922	87,7	8673		43,1		0,595		1351
								360	922	88,7	8695						1388
								378	922	89,1	8693						1388
								433	922	90,2	8707						1388
								506	922	91,4	8716						1388
								596	922	92,4	8706						1389
L		325	361	379	434	507	598	295	845	87,3	8673		48,6		0,844		1234
								329	845	88,4	8697						1373
								345	845	88,8	8683						1442
								396	845	90,0	8711						1572
								462	845	91,2	8703						1572
								546	845	92,2	8719						1572
M		298	332	349	400	468	553	271	787	86,1	8678		58,5		0,799		1133
								302	787	87,3	8683						1262
								318	787	87,8	8699						1327
								364	787	89,0	8691						1513
								427	787	90,3	8716						1513
								504	787	91,5	8710						1513